CBEYOND COMMUNICATIONS

VOICE CONFIGURATION
DIGITAL INTERFACE (T1 CAS)

(E)

This form needs to be completed by the customer or customer's vendor. Please Fax completed form to Cbeyond at 678-424-2770.

Customer Profile

COMPANY NAME	VENDOR NAME
WHERE IS THE PHONE EQUIPMENT LOCATED?	VENDOR CONTACT NAME
PLEASE NOTE SPECIFIC LOCATION FOR EXTENDED CIRCUIT DEMARC.	VENDOR CONTACT SIGNATURE

Standard Configuration

Cbeyond provides the following standard configuration for a Digital (CAS) interface:

- o 1 Combo (2-way) Trunk Group
- o ESF framing; B8ZS coding
- o E&M Wink Signaling
- o Glare and Clocking – Cbeyond Network is Master
- o DTMF Dialing
- o Trunk Selection: Ascending - Inbound
  Descending - Outbound
- o All DIDs and phone numbers are pointed to the 1 Trunk Group

Cbeyond will configure your voice services according to the specifications you provide. It is you or your phone vendor's responsibility to ensure the phone equipment is set to accept this configuration.

Important Notes

- o No testing environment is provided
- o Phone numbers are ported on the Service Activation date (install), after Cbeyond's equipment is installed. Rescheduling Phone number porting may result in an additional charge.
- o The installation event requires approx 4 hours
- o Phone vendor must provide a T-1 Crossover cable to connect customer's phone system to the digital interface on Cbeyond's equipment.
- o Channel banks are not supported

Cbeyond's Digital/CAS interface does not provide calling features such as Call Forwarding.
These features must be provided by the customer's phone system. This includes Call Forwarding to Voice Mail.

Digital Trunk Configuration

ELEMENT	SELECTION	NOTES
How many trunk lines are required? (enter #) →		o min of 9 lines for BeyondVoiceI; 15 for BeyondVoiceII
What Telephone Number should be the Trunk Group Number? (Enter phone number) →		o **This number will be displayed for caller ID on outbound calls** o All calls will be sorted under this number on the invoice
Are Account Codes needed on the Trunk Group? (Yes or No) →		o All lines in the Trunk Group will require Account Code entry

Customer Phone Equipment

Select one:	System Manufacturer:	System Model #:
PBX ☐ Key System ☐ Hybrid Key System ☐		

OTHER IMPORTANT NOTES:

[1] All trunk groups will receive 900/976 Blocking and Collect/3rd Party Blocking.

2 Cbeyond does not offer access to dial-around numbers, such as 10-10-xxx.